

06/16/00
JC862 U.S. PTO

By Express Mail #EL489906390US

Attorney Docket No.: 2132-32PCON

Check box if applicable: ☐ DUPLICATE

UTILITY PATENT APPLICATION TRANSMITTAL

Submit an original and a duplicate for fee processing

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

JC812 U.S. PTO
09/595828
06/16/00

Assistant Commissioner for Patents
BOX PATENT APPLICATION
Washington, DC 20231

Dated: June 16, 2000

Sir:

Transmitted herewith for filing is the utility patent application of:

Inventor(s): Sami ALA-LUUKKO, Juho HUOPANIEMI, Olli PERÄ

For: Method and System for the Transmission and Modification of Intelligent Network Parameters

Enclosed are:

- Transmittal letter (2x) with Fee Computation Sheet
- General Authorization For Payment of Fees (2x)
- Title Page, Specification, Claims 1 to 34 & Abstract (25 pages)
- Unexecuted Declaration and Power of Attorney (3 p.)
- Two (2) sheets of drawings (Figs. 1 to 3)
- Check for \$ 1176 for filing fee
- Information Disclosure Statement
- PTO Form 1449 with copies (5 docs.) of cited references
- Return Receipt Postcard

☐ Please charge my Deposit Account No. 03-2412 in the amount of \$_. A duplicate copy of this sheet is enclosed.

☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this application or credit any overpayment to Deposit Acct. No. 03-2412.

☒ Any additional filing fees required under 37 CFR 1.16.

☒ Any patent application processing fees under 37 CFR 1.17

By Express Mail #EL489906390US

- [x] The issue fee set in 37 CFR 1.18 at 3 months from mailing of the Notice of Allowance, pursuant to 37 CFR 1.311 (b) provided the fee has not already been paid by check.
- [x] Any filing fees under 37 CFR 1.16 for presentation of extra claims.

[x] Priority is claimed for this invention and application, corresponding applications having been filed in **Finland** on **December 16, 1997**, No. **974531**, **Finland** on **December 22, 1997**, No. **974604**, and in **International Application No. PCT/FI98/00983** filed **December 15, 1998**, respectively.

Respectfully submitted,
COHEN, PONTANI, LIEBERMAN & PAVANE

By: 

Lance J. Lieberman
Reg. No. 28,437

551 Fifth Avenue, Suite 1210
New York, New York 10176
Tel: (212) 687-2770
Fax: (212) 972-5487

**APPLICATION FOR UNITED STATES
LETTERS PATENT**

**METHOD AND SYSTEM FOR TRANSMISSION AND MODIFICATION OF
INTELLIGENT NETWORK PARAMETERS**

Inventor(s):

**Sami ALA-LUUKKO
Juho HUOPANIEMI
Olli PERÄ**

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 The present invention relates to telecommunication systems. In particular, the invention relates to a method and system for modification and transmission of intelligent network service data and/or service data parameters by means of another telecommunication network.

2. Description of Related Art

10 At present, operators of both wired and mobile telephone networks commonly provide a wide variety of optional or otherwise-available services to their subscribers, such for example as permanent or remotely controlled call transfer, call waiting, suppression of number display (i.e. calling number blocking), advance notice of billing to the subscriber, and like services. These services are generally available at the option of the subscriber, so that the subscriber can decide if and when to use each service. In addition, intelligent network systems
15 utilize a number of other parameters that are preferably modified directly by the subscriber without requiring action by the teleoperator or service provider which would necessitate the use of customer service resources.

20 In one known system the parameters of intelligent network services are remotely modified via the Internet; this implementation requires, however, that the user have Internet access. Another prior art solution uses a menu service based on tone frequency signals that the user is prompted to input, but relies on a difficult user interface and is slow in use. Moreover,

long numerical sequences such as those commonly used in such systems are difficult to visualize, and the SSP centers employed in intelligent network applications are usually able to identify tone frequency signals during call setup but not during the ensuing or resulting call.

The known CAMEL (Customized Applications for Mobile Network Enhanced Logic) architecture utilizes a USSD (Unstructured Supplementary Service Data) based user interface to provide operator-specific intelligent network services, even for subscribers who have moved outside of or beyond the mobile communication network of their home operator under the international roaming system. USSD operations can be used to transmit unstructured supplementary service data between a mobile station and the telecommunication network. The USSD-based user interface that is utilized in conjunction with the CAMEL architecture requires that the service control point (SCP) of the mobile communication network support the MAP (Mobile Application Part) interface in question.

OBJECTS AND SUMMARY OF THE INVENTION

It is accordingly the *desideratum* of the present invention to eliminate or at least significantly reduce the drawbacks and deficiencies of the prior art, as for example described hereinabove.

It is a particular object of the invention to provide a new method and system to enable a user to remotely control intelligent network services by means of a terminal device connected to another telecommunication network.

The present invention is thus directed to, *inter alia*, a method for modifying and transmitting intelligent network service data or service parameters in a telecommunication system comprising an intelligent network, a second telecommunication network and means for connecting the intelligent network to the second telecommunication network. The intelligent network includes a service control point (SCP) and a service data point (SDP). In the inventive method, the second telecommunication network is connected via a gateway to the service logic of the service control point and/or to the service data point. A service data parameter and/or the service logic of the intelligent network is modified using a protocol supported by the second telecommunication network. In a preferred implementation, a conversion between a fixed-format message as used in the second telecommunication network and a message format supported by the intelligent network is performed by using a table in the gateway.

In a preferred embodiment, the service data parameter and/or the service logic is/are modified via a write operation performed by the gateway in the service logic of the service control point and/or in the service data point. The second telecommunication network is, in accordance with the invention, preferably an IP (Internet Protocol) based network such as the Internet, or a digital mobile communication network such as a GSM (Global System for Mobile Communications) network.

The invention additionally provides a method in which, in a telecommunication system as described above, the second telecommunication network is connected via the gateway to the service logic of the service control point of the intelligent network, and the intelligent network service data parameter or service logic is modified using a protocol supported by the second telecommunication network. In an embodiment of this method, a conversion between a fixed-format message¹ as used in the second telecommunication network and a message format supported by the service control point of the intelligent network is performed using a table in the gateway. The service data parameter and/or service logic is preferably modified via a write operation performed by the gateway in the service logic of the intelligent network service control point.

The invention further provides a method for modifying an intelligent network service parameter in a telecommunication system as described above, in which the service parameter is transmitted using a terminal device in the form of a text message to the gateway, and the text message is converted in the gateway into the format of an intelligent network service parameter and transmitted to the data point of the intelligent network. In an

embodiment of this method, an acknowledgement message is returned from the intelligent network data point to the gateway, and the acknowledgement message is converted into the form of a text message and sent to the terminal device. The record to be modified in the intelligent network data point is preferably identified in the gateway by the calling subscriber number transmitted in the text message signaling. The record to be modified in the intelligent network data point may also be identified in the gateway by the contents of the text message.

In various respective implementations, the information may be transmitted between the terminal device and the gateway in the form of a short message, or by using the USSD-MAP protocol, or by using the WAP (Wireless Application Protocol) protocol. In a GSM mobile telephone system, the short-message service allows transmission of text messages from a mobile station to another terminal even if the receiver is not reachable at that time, and a text message sent as a short message may have a maximum length of 160 characters. The WAP protocol defines a standard for applications that provide services for wireless network terminal equipment; by using WAP, it is possible to connect, as for example with Internet servers, by telephone.

The invention is additionally directed to a telecommunication system for modification and transmission of intelligent network service data or service parameters, the system comprising an intelligent network, a second telecommunication network and means for connecting the intelligent network to the second telecommunication network. The intelligent network includes a service control point and a service data point. The system further comprises a gateway for connecting the second telecommunication network to the service logic

of the service control point and/or to the service data point of the intelligent network, and means for modification of a service data parameter and/or the service logic of the intelligent network using a protocol supported by the second telecommunication network. In one embodiment, the gateway comprises table means for performing or implementing a conversion
5 between a fixed-format message supported by the second telecommunication network and a message format supported by the intelligent network. The gateway preferably comprises means for carrying out a write operation in the service logic of the service control point or in the service data point of the intelligent network, and means for modification of the service data parameter and/or service logic. The second telecommunication network in the system of the invention is, by way of preferred example, an IP-based network or a digital mobile telephone
10 network.

The present invention also provides a telecommunication system for modification of intelligent network services or service logic, the system comprising an intelligent network, a second telecommunication network and means for connecting the
15 intelligent network to the second telecommunication network. The intelligent network includes a service control point. The system further comprises a gateway for connecting the second telecommunication network to the service logic of the service control point of the intelligent network and means for modification of a service data parameter and/or the service logic of the intelligent network using a protocol supported by the second telecommunication network. The
20 gateway preferably comprises table means for performing or implementing a conversion between a fixed-format message supported by the second telecommunication network and a

message format supported by the intelligent network. In one embodiment, the gateway comprises means for carrying out a write operation in the service logic of the service control point of the intelligent network and means for modification of the service data parameter and/or service logic. The second telecommunication network in the system is preferably, by way of example, an IP-based network or a digital mobile telephone network.

The invention additionally provides a telecommunication system for modification of an intelligent network service parameter, said system comprising an intelligent network, a digital mobile telephone network, means for connecting the intelligent network to the mobile telephone network, and terminal equipment connected to the mobile telephone network. The intelligent network includes a service data point. The system further comprises means for sending a service parameter in the form of a text message from the terminal equipment to a gateway, and means for converting the text message in the gateway into the format of an intelligent network service parameter and transmitting it to the data point of the intelligent network. The system preferably includes means for returning an acknowledgement message from the intelligent network data point to the gateway, and means for converting the acknowledgement message in the gateway into the form of a text message and sending it to the terminal equipment.

In a preferred embodiment of this inventive system, the gateway comprises means by which the intelligent network data point record to be modified is identified by the calling subscriber number, i.e. the A-number, which is transmitted in the text message signaling. In another embodiment, the system comprises means for identifying the record by

the contents of the text message. The system preferably includes means for transmitting information from the terminal equipment to the gateway, as for example in the form of a short message, using the USSD or the WAP protocol.

The present invention advantageously enables implementation of the user interface between intelligent network services and the user with the existing service development properties of the service control point. The user interface can accordingly be implemented in a significantly more flexible manner than by identification of tone frequency signals, as in the prior art. Using the short message service, a mobile telephone subscriber can modify his or her services at any time that the user is reachable via the telecommunication network. The invention also permits communication between a GSM subscriber and an intelligent network in a telecommunication network other than the GSM network, as for example the service logic of a wired telephone network.

Other objects and features of the present invention will become apparent from the following detailed description considered in conjunction with the accompanying drawings.

It is to be understood, however, that the drawings are designed solely for purposes of illustration and not as a definition of the limits of the invention, for which reference should be made to the appended claims.

DETAILED DESCRIPTION OF THE CURRENTLY PREFERRED EMBODIMENTS

Shown by way of example in Fig. 1 is an illustrative signaling procedure and methodology in accordance with the invention between a service control point SCP of an intelligent network and a subscriber/user's terminal equipment TE. The gateway GW includes means for its connection to the service control point SCP and to a second telecommunication network 1 (Fig. 3). The second telecommunication network 1 may, for example, be a digital mobile communication network or the Internet. When the service control point SCP sends information or a request to the terminal equipment TE, it is transmitted to the gateway GW, as for example using a WRITE message. If the gateway GW supports transmission of information, such as in text form, then the service control point can generate this type of information itself, in which case the gateway GW will only have to convert the information into a form or format compatible with the properties of the second telecommunication network 1. In one currently-contemplated embodiment, the service control point SCP indicates, using a suitable indicator such as a number, a list in the gateway GW to define the type of message being transmitted. This procedure is particularly advantageous when the particular gateway GW does not support any other form or transmission of numeric data. The gateway thus sends the information DATA via the second telecommunication network 1 to the terminal equipment TE.

To transmit the information DATA from the user's terminal equipment TE to the service control point SCP, the user applies network-specific properties. In the GSM system, for example, such a property may be a short message or USSD. The second telecommunication

network 1 transmits this information DATA to the gateway GW, which modifies it into a database interface operation understood by the service control point SCP. If the service control point SCP does not support transmission of data other than numeric information, then gateway GW may be provided with a table for converting fixed-format messages into database interface operations.

5 In the signaling example of Fig. 2, an intelligent network service parameter is changed using the short-message service of a digital mobile telephone network. The user sends a short message to a service number. The short message contains fixed-format information for modifying the service parameter. For example, the letter "D" may denote deactivating of the intelligent network service parameter, and the letter "A" may denote activating of the parameter.

10 In the operator's network, the short message is transmitted to the gateway GW, which updates the relevant data in the database of the service data point SDP. A subscriber in the digital mobile telephone network sends a short message, which is transmitted in accordance with the GSM standard, to a short message service center SC. The short message service center SC sends the message to the SMS-GMSC, which performs an HLR (Home Location Register) inquiry based on

15 the B-number defined by the subscriber. The Home Location Register HLR may for example be a GSM system database containing information that includes subscriber data, subscriber location data, call control data, short-message services and billing data. The "B-number" identifies the receiver of the short message.

In this illustrative situation, the subscriber has selected a B-number value that

20 points to a specific gateway GW. Gateway GW receives the short message sent by the SMS-GMSC and examines the A-number contained therein to determine the subscriber whose

intelligent network parameters it has to change. By using this information and analyzing the contents of the short message, the gateway GW knows which record in the database of the services data point SDP is to be changed. Gateway GW then performs a WRITE operation that the service data point in question will understand. When the intelligent network service is next
5 activated, the service control point SCP can check the user-defined parameter value in the service data point SDP.

Fig. 2 represents an exchange of messages between the Home Location Register HLR of the SMS-GMSC and the gateway GW in accordance with the GSM MAP protocol. The write operation of the database interface being used is applied between the gateway GW and the
10 service control point SCP. The two lowermost messages shown in Fig. 2 are applied if, as in the figure, the calling subscriber is to be given optional information as to whether or not the database write operation was successful.

In an embodiment of the invention, the gateway GW is also operable for responding to an MAP-SendRoutingInfoForSM inquiry with its own address, in which case the
15 SMS-GMSC sends the short message to gateway GW. All of the functionalities associated with the service are now in the same database interface.

Figs. 3 diagrammatically depicts a system implementation in accordance with the present invention. The terminal device TE is connected via the second telecommunication network 1 to the gateway GW. The terminal equipment TE comprises means 13 for transmitting
20 a service parameter in the form of a text message SMS to the gateway GW. The text message SMS may be a short message or, by way of example, a message consistent with the USSD or

WAP protocol, a byte-oriented or a document-oriented message. Gateway GW is connected to the network components of or associated with or forming the intelligent network IN, the service control point SCP and the service data point SDP.

Gateway GW comprises means 9 and 14 for modification of an intelligent network service data parameter and/or service logic using a protocol supported by the second telecommunication network 1. Gateway GW further comprises table means 10 for performing or implementing a conversion between a fixed-format message supported by the second telecommunication network 1 and a message format supported by the intelligent network IN. Means 11 are used to carry out the write operation and means 12 to modify the data in the service logic of the service control point SCP and/or in the service data point SDP. Using means 15, the service data point returns an acknowledgement message to gateway GW, which includes means 16 for further converting the acknowledgement message into text message format and sending it to the terminal equipment TE. Means 19 are used to transmit information between the terminal equipment TE and the database interface in the form of a short message, means 20 using the USSD protocol and means 21 using the WAP protocol. To identify the record to be modified in the service data point SDP, gateway GW utilizes means 17 for identification by the A-number and means 18 for identification by the contents of the text message.

The functionality of gateway GW is seen by service control point SCP as that resembling service data point SDP. Data flowing through the database interface is simple numeric data, which is converted by gateway GW into a fixed-format message and applied to the interface connecting to the second telecommunication network 1. The gateway may be

implemented as an independent device or as a part of the service control point SCP or the service data point SDP. The invention can be implemented, as a general matter of design choice, in many types of systems supporting SS7 and/or other protocols.

Thus, while there have shown and described and pointed out fundamental novel features of the invention as applied to preferred embodiments thereof, it will be understood that various omissions and substitutions and changes in the form and details of the methods described and devices illustrated, and in their operation, may be made by those skilled in the art without departing from the spirit of the invention. For example, it is expressly intended that all combinations of those elements and/or method steps which perform substantially the same function in substantially the same way to achieve the same results are within the scope of the invention. Moreover, it should be recognized that structures and/or elements and/or method steps shown and/or described in connection with any disclosed form or embodiment of the invention may be incorporated in any other disclosed or described or suggested form or embodiment as a general matter of design choice. It is the intention, therefore, to be limited only as indicated by the scope of the claims appended hereto.

CLAIMS

We is claimed is:

5 1. A method for modifying and transmitting one of intelligent network
service data and service parameters in a telecommunication system comprising an intelligent
network, a service control point of the intelligent network, a service data point of the
intelligent network, a second telecommunication network, and means for connecting the
intelligent network to the second telecommunication network, comprising the steps of:

10 connecting the second telecommunication network to one of a service
logic system of the service control point and the service data point of the intelligent network
via a gateway; and

15 modifying one of a service data parameter and service logic of the
service logic system of the service control point using a protocol supported by the second
telecommunication network.

2. The method of claim 1, further comprising the step of performing a
conversion, using a table in the gateway, between a fixed-format message used in the second
telecommunication network and a message format supported by the intelligent network.

3. The method of claim 1, wherein said modifying step further comprises modifying in one of the service logic of the service control point and the service data point, via a write operation performed by the gateway, the one of the service data parameter and the service logic.

5

4. The method of claim 1, wherein the second telecommunication network comprises an IP-based network.

5. The method of claim 1, wherein the second telecommunication network comprises a digital mobile telephone network.

6. A method for modifying one of intelligent network services and service logic in a telecommunication system comprising an intelligent network, a service control point of the intelligent network, a second telecommunication network, and means for connecting the intelligent network to the second telecommunication network, comprising the steps of:

connecting the second telecommunication network to service logic of the service control point of the intelligent network via a gateway; and

modifying one of a service data parameter and the service logic of the intelligent network using a protocol supported by the second telecommunication network.

20

7. The method of claim 6, further comprising the step of performing a conversion, using a table in the gateway, between a fixed-format message used in the second telecommunication network and a message supported by the service control point of the intelligent network.

5

8. The method of claim 6, wherein said modifying step further comprises modifying in the service logic of the service control point, via a write operation performed by the gateway, the one of the service data parameter and the service logic.

9. The method of claim 6, wherein the second telecommunication network comprises an IP-based network.

10. The method of claim 6, wherein the second telecommunication network comprises a digital mobile telephone network.

11. A method for modifying an intelligent network service parameter in a telecommunication system comprising an intelligent network, a service data point of the intelligent network, a digital mobile telephone network, a gateway for connecting the intelligent network to the mobile telephone network, and a terminal device connected to the mobile telephone network, comprising the steps of:

transmitting the service parameter, as a text message by means of the terminal device, to the gateway;

converting, in the gateway, the transmitted text message to a service parameter format of the intelligent network; and

5 transmitting the converted service parameter from the gateway to the service data point.

12. The method of claim 11, further comprising the steps of:

10 returning an acknowledgement message from the service data point to the gateway in response to receipt by the service data point of the converted service parameter;

converting, into a text message format, the converted service parameter received by the service data point; and

15 transmitting the text message format converted service parameter from the service data point to the terminal device.

13. The method of claim 11, further comprising the step of identifying, in the gateway, a record to be modified in the service data point by using a calling subscriber number of the text message transmitted by means of the terminal device.

14. The method of claim 11, further comprising the step of identifying, in the gateway, a record to be modified in the service data point by using contents of the text message transmitted by means of the terminal device.

5 15. The method of claim 11, wherein text messages are transmitted between the terminal device and the gateway as short messages.

16. The method of claim 11, wherein information is transmitted between the terminal device and the gateway using USSD protocol.

17. The method of claim 11, wherein information is transmitted between the terminal device and the gateway using WAP protocol.

18. In a telecommunication system for modification and transmission of one
15 of intelligent network service data and service parameters and that includes an intelligent network, a service control point of the intelligent network, a service data point of the intelligent network, a second telecommunication network, and means for connecting the intelligent network to the second telecommunication network,

a gateway for connecting the second telecommunication network to one
20 of service logic of the service control point and the service data point of the intelligent network; and

means for modifying one of a service data parameter and the service logic of the service control point using a protocol supported by the second telecommunication network.

5 19. In the system of claim 18, said gateway comprising table means for performing a conversion between a fixed-format message supported by the second telecommunication network and a message format supported by the intelligent network.

10 20. In the system of claim 18, said gateway comprising means for carrying out a write operation in one of the service logic of the service control point and the service data point, and second means for modifying one of the service data parameter and the service logic.

15 21. In the system of claim 18, the second telecommunication network comprising an IP-based network.

 22. In the system of claim 18, the second telecommunication network comprising a digital mobile telephone network.

20 23. In a telecommunication system for modification of one of intelligent network services and service logic and including an intelligent network, a service control point

of the intelligent network, a second telecommunication network, and means for connecting the intelligent network to the second telecommunication network,

a gateway for connecting the second telecommunication network to service logic of the service control point of the intelligent network; and

5 means for modifying one of a service data parameter and the service logic of the intelligent network using a protocol supported by the second telecommunication network.

10 24. In the system of claim 23, said gateway comprising table means for performing a conversion between a fixed-format message supported by the second telecommunication network and a message format supported by the intelligent network.

15 25. In the system of claim 23, said gateway comprising means for carrying out a write operation in the service logic of the service control point, and second means for modifying one of the service data parameter and the service logic.

26. In the system of claim 23, wherein the second telecommunication network comprises an IP-based network.

20 27. In the system of claim 23, wherein the second telecommunication network comprises a digital mobile telephone network.

28. In a telecommunication system for modifying an intelligent network service parameter and including an intelligent network, a service data point of the intelligent network, a digital mobile telephone network, a gateway for connecting the intelligent network to the mobile telephone network, and terminal equipment connected to the mobile telephone network,

means for transmitting the service parameter, as a text message, from the terminal equipment to the gateway; and

means, in the gateway, for converting the transmitted text message to a service parameter format of the intelligent network and for transmitting the converted service parameter from the gateway to the service data point.

29. In the system of claim 28,

means for returning an acknowledgement message from the service data point to the gateway in response to receipt by the service data point of the converted service parameter; and

second means for converting, into a text message format, the converted service parameter received by the service data point and for transmitting, from the service data point to the terminal equipment, the text message format converted service parameter.

30. In the system of claim 28, said gateway comprising means for identifying a record in the service data point to be modified using a calling subscriber number of the text message transmitted from the terminal equipment.

5 31. In the system of claim 28, said gateway comprising means for identifying a record in the service data point to be modified using contents of the text message service parameter.



10 32. In the system of claim 28, means for transmission of information between the terminal equipment and the gateway using short messages.

15 33. In the system of claim 28, means for transmission of information between the terminal equipment and the gateway using USSD protocol.

34. In the system of claim 28, means for transmission of information between the terminal equipment and the gateway using WAP protocol.

5

10






Fig. 3

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

METHOD AND SYSTEM FOR THE TRANSMISSION AND MODIFICATION OF INTELLIGENT NETWORK PARAMETERS

the specification of which is attached hereto.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, Section 1.56(a).

I also acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37 CFR 1.63(d), which occurred between the filing date of the prior application and the filing date of the continuation-in-part application, if this is a continuation-in-part application.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application:	Country:	Finland
	Appln. No.:	974531
	Filed:	December 16, 1997

Prior Foreign Application:	Country:	Finland
	Appln. No.:	974604
	Filed:	December 22, 1997

Prior Foreign Application:	Country:	PCT
	Appln. No.:	PCT/FI98/00983
	Filed:	December 15, 1998

I hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

MYRON COHEN, Reg. No. 17,358; THOMAS C. PONTANI, Reg. No. 29,763; LANCE J. LIEBERMAN, Reg. No. 28,437; MARTIN B. PAVANE, Reg. No. 28,337; MICHAEL C. STUART, Reg. No. 35,698; KLAUS P. STOFFEL, Reg. No. 31,668; EDWARD M. WEISZ, Reg. No. 37,257; JULIA S. KIM, Reg. No. 36,567; VINCENT M. FAZZARI, Reg. No. 26,879; ALFRED W. FROEBRICH, Reg. No. 38,887; KENT H. CHENG, Reg. No. 33,849; GEORGE WANG, Reg. No. 41,419; TZVI HIRSHAUT, Reg. No. 38,732, GERALD J. CECHONY, Reg. No. 31,335 and ROGER S. THOMPSON, Reg. No. 29,594.

Address all telephone calls to Lance J. Lieberman, Esq. at telephone No. (212) 687-2770.

Address all correspondence to:

Lance J. Lieberman, Esq.
Cohen, Pontani, Lieberman & Pavane
551 Fifth Avenue, Suite 1210
New York, New York 10176

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole or First Inventor: Sami ALA-LUUKKO

Inventor's signature: _____

Dated: _____
Month/Day/Year

Residence: **Paraistentie 18 A 2, FIN-00280 Helsinki, Finland**

Citizenship: **Finland**

Post Office Address: **Paraistentie 18 A 2
FIN-00280 Helsinki, Finland**

Full Name of Second Joint Inventor: Juho HUOPANIEMI

Inventor's signature: _____

Dated: _____
Month/Day/Year

Residence: **Ruutikellarinkuja 4 B 18, FIN-02600, Espoo, Finland**

Citizenship: **Finland**

Post Office Address: **Ruutikellarinkuja 4 B 18
FIN-02600, Espoo, Finland**

Full Name of Third Joint Inventor: Olli PERÄ

Inventor's signature: _____

Dated: _____
Month/Day/Year

Residence: **Candelinintie 4 B 5, FIN-90570, Oulu, Finland**

Citizenship: **Finland**

Post Office Address: **Candelinintie 4 B 5
FIN-90570, Oulu, Finland**